



END OF LIFE

55" FHD 350 nit Professional Indoor Panel

LTI550HN15

LTI550HN15 is a color active matrix liquid crystal display composed of a TFT LCD panel, a driver circuit, and a backlight unit. This brand new, 55" value panel brings advanced, crystal-clear image quality and true color expression with the deepest blacks for remarkable content delivery. Complement any interior with this slim design - deliver brilliant visual messages anywhere - retail locations, airports, hotels, restaurants, hospitals and corporate environments.

To find a distributor or request a sample [Contact Us](#)



Value and professional performance for indoors

Outstanding color and performance

- Full HD resolution guarantees clearer image with life-like detail for an immersive experience
- Enhanced contrast ratio (4,000:1) ensures unprecedented quality and razor-sharp pictures
- 16.7 Million colors (72% NTSC) provides true-color representation for vivid graphics
- Proprietary optical film treatment enhances anti-glare display performance in bright ambient light conditions
- Wide viewing angle 178° ensures broader engagement per installation

Unrivalled durability and reliability

- 0.38 inches thin - this ultra-slim design - complements any interior and seamlessly blends providing greatest design flexibility and rich visual appeal
- Proprietary TFT and liquid crystal solutions to prevent black mura blackening even after long periods of use
- Professional panel quality ensures long operational life and low total cost of ownership
- Energy efficient edge- LED design ensures low maintenance cost and higher ROI per installation
- Eco-friendly material composition certified by RoHS

Features:

**✖ Optical**

- Full HD (1,920 x 1,080) resolution (16:9)
- High contrast ratio (4,000:1)
- High aperture ratio and wide color gamut coverage (NTSC 72%)
- Wide viewing angle (178°)
- Anti-glare surface treatment (1% haze)
- Fast response time - gray-to-gray (G-to-G) 8 ms
- Super Vertical Alignment (SVA) mode

✖ Reliability

- Normal Tni (75°C) liquid crystal
- Black mura prevention technology

✖ Warranty

- 8 hr daily operation for 18 months

✖ Design

- Landscape orientation only
- Even 8.9 mm bezel
- Edge LED backlight

✖ Electrical

- Low power consumption
- Low Voltage Differential Signaling (LVDS) interface
- Data Enable (DE) mode

✖ Certifications

- RoHS compliant (Pb-free)
- UL/CB

Specifications:

Panel Type	55" FHD	Outline Dimensions (W/H/D)	1,235.4 x 706.2 x 9.7 mm
Native Resolution	1,920 x 1,080 (FHD)	Aspect Ratio	16:9
Brightness	350 nit	Contrast Ratio	4,000:1
Thickness (Body)	9.7 mm	Color Gamut	NTSC 72%
Viewing Angle	178°	Orientation	Landscape
Response Time (G-to-G)	8 ms	Operation Time	8 hr